



# Sherman Heavy Duty

Specifications for Sherman Task Model HD9000 and Sherman Drafting Stool Model HD9000DS  
Specifications generated from the standard configuration

## DIMENSIONS



Model HD9000



Model HD9000DS

MODEL	HD9000	HD9000DS
<b>OVERALL</b>		
Width (Outer armrest to outer armrest)	29"-32"	29"-32"
Depth (Front of seat to back of back rest)	22"-24"	22"-24"
Height (Floor to top of backrest)	41.5"-47"	44"-52"
Seat Width	23"	23"
Back Width	22"	22"
Back Height (from compressed seat)	24"	24"
Seat Height	20.5"-26"	23"-31"
Seat Depth Adjustment	2" range	2" range
Arm Width (Inner arm pad to inner arm pad)	21"-24"	21"-24"
Arm Height (Compressed seat to top of armrest)	8"-12"	8"-12"

## FEATURES

### Lumbar Support

Static Lumbar Support Located at 5.5" to 12.5" above compressed seat height.

### FA Arms

Heavy duty steel fold away arms that are width and height adjustable. Arm folds forward or back to a 90° with the chair. Topped with ultra-comfortable polyurethane arm pads.

### Base and Casters

28" 5 star structurally engineered base with 3" casters or glides. HD9000DS features a height adjustable foot ring.

### Mechanism

Swivel mechanism with a 2" seat depth adjustment.

### Standard Configuration

Upholstered seat and back with black frame and base.

### Other Features

Reinforced steel seat and back bar. Weight rating of 450 lbs. and designed for 24/7 applications. Oversized molded foam seat pan with waterfall edge. CAL 117.

**ISO 14001 Certified**  
**ISO 9001 Certified**

© 2014 Nightingale Corp. All Rights Reserved



Schedule



Tel Toll Free: 1.800.363.8954  
Fax Toll Free: 1.800.637.6784  
Email: info@nightingale.com  
Website: www.nightingalechairs.com